

## Technical Data Sheet

# GLEIVO Beeswax No. 317

<b>N</b> means	<b>LIVOS neutral</b> for the allergy-prone and chemically sensitive
<b>Application range</b>	For interior use, in order to finish surfaces treated with LIVOS oils. To refresh waxed timber, cork and stone surfaces, such as floors, paneling and furniture. For regular care of linoleum. Not suitable for areas exposed to water splashes.
<b>Technical qualities</b>	Liquid, easy to apply and very high yield. Applicable by airless spraying. Produces a silky glossy finish when completely dry.
<b>Full declaration</b>	Beeswax, shellac wax, carnauba wax, walnut oil, isoaliphates, alumina and drying agents free of lead.
<b>Color</b>	Clear. Coloration is possible with max. 10% of VINDO Natural Gloss Paint No. 650.
<b>Dilution</b>	Ready to use.
<b>Application method</b>	By brushing, spraying or with a lint-free cloth at temperatures above 12 °C (54 °F).
<b>Coverage</b>	For surface treatment: 1 liter (1.06 quart) is sufficient for approximately 25 m <sup>2</sup> (269 ft <sup>2</sup> ), i.e. 40 ml/m <sup>2</sup> ; could be considerably less, depending on the condition and absorbency of the surface. Always do a test application! For surface care: 1 liter (1.06 quart) is sufficient for an average of 100 m <sup>2</sup> (1076 ft <sup>2</sup> ), i.e. 10 ml/m <sup>2</sup> .
<b>Drying time</b>	At 23° C (73 °F) and 50% relative humidity, approximately 2 - 4 hours.
<b>Cleaning</b>	Clean equipment immediately after use with SVALOS Thinner No. 292.
<b>Specific gravity</b>	0.78 g/ml.
<b>Safety advice</b>	<p>Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with GLEIVO Beeswax No. 317 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content.</p> <p>The product itself will not combust spontaneously. Contains Cobalt (+2) salts. Can cause allergic reactions. S 2 Keep out of the reach of children. S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label</p>
<b>Disposal</b>	According to locally regulated laws.
<b>Container sizes</b>	0.25 l; 1 l; 2.5 l; 10 l; 30 l.
<b>Storage</b>	Cool and dry. Shelf life: unopened at least 2 years. Close lid tightly after use.
<b>Packaging</b>	Made of polyethylene (PE). This material is ground water neutral and recyclable.  See reverse for application instructions.

## How to use

# GLEIVO Beeswax No. 317

Hypoallergenic- without orange oil

- Preparation** The surface must be dry, solid, clean, and free of grease and dust. Surface must be pre-treated with LIVOS oils, e.g. MELDOS Natural Resin Hardening Oil No. 265 or LIVOS stains. To ensure compatibility on surfaces previously treated with products from another manufacturer, do a test application on an inconspicuous area.
- Application** Shake or stir product thoroughly before use. Apply GLEIVO Beeswax No. 317 very thinly and evenly with a brush or cloth. After approximately 2 - 4 hours, polish (with wood in the direction of the wood grain) with a wadded cloth, a wax brush or a floor polisher.
- Important tips** Ensure good ventilation during application and drying times. A very thin coating of the beeswax on surfaces with a high electrostatic charge (artificial resin varnishes, etc.) will significantly reduce static electricity on those surfaces.
- Cleaning** Remove dust with a vacuum cleaner or mop. Rubber abrasion and stubborn dirt can be removed with SVALOS Thinner No. 222. Clean with TRENA pH-Neutral Cleaner No. 556 according to demand.
- Care** According to usage, apply an after-treatment with GLEIVO Beeswax No. 317 or with BIVOS Oil Wax No. 375 once or twice a year.

**These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.**

November 2008 Rev. 2.2

LIVOS Plant Chemistry D-29568 Wieren · Tel. +49 5825 / 88-0 · Fax 88-60 · [www.livos.de](http://www.livos.de) · [info@livos.de](mailto:info@livos.de)