

Technical Data Sheet

GLOUROS Natural Siding & Masonry Cleaner No. 1806

PDF	GLOUROS Natural Siding & Masonry Cleaner No. 1806
Application range	For interior and exterior wooden- and stone surfaces such as tiles, tombstones, walls, and facades. Not suitable for marble, calcareous stone or other material sensitive to acid e.g. terrazzo.
Technical qualities	Removes chalk- and cement residue, moss, algae, stains of fungi, salt deposits on facade boards. Dissolves oil, fat- and protein soiling, completely or partly, depending on the surface.
Full declaration	Water, citric acid and Reetha extract.
Colors	Clear.
Dilution	Depending on the density and the amount of soil, dilute with water at the ratio of 1:10 for cleaning and at the ratio of 1:5 for after-treatment.
Application method	With a sponge, a spray bottle, or a high pressure cleaner.
Cleaning	Clean tools immediately after use with plenty of water.
Specific gravity	1.09 g/ml.
Safety advice	Keep out of the reach of children. Product reacts acidic. Protect skin and eyes during application. In case of contact, rinse off with plenty of water. In case of eye contact, seek medical advice immediately. Non-ionic surfactants: less than 5%.
Disposal	According to locally regulated laws.
Container sizes	1.0 l; 10 l; 30 l.
Storage	Cool and dry. Please see label for expiry date.

Important tips

GLOUROS Natural Siding & Masonry Cleaner No. 1806

Application Apply GLOUROS Natural Siding & Masonry Cleaner No. 1806 with a sponge or a spraying device on the surface to be treated. Rub the dirt off with a non-abrasive pad (normally white) or a sponge and flush or rinse with plenty of water.

Fungi, moss, algae Dilute GLOUROS Natural Siding & Masonry Cleaner No. 1806 with water, at a ratio of 1: 10 and remove dirt. To protect the surface against new fungi spray again with a dilution of 1: 5 and allow to dry.

Salt deposits on facades Before applying GLOUROS No. 1806, the surface should be watered well. Spray surface with a 1: 20 dilution. Rinse off with plenty of water and low pressure.

Metals

Clean light mineral soiling on brass, copper and stainless steel with a dilution of 1: 5 to 1: 20. Do not rinse off cleaned stainless steel surfaces. Remove chalk residue on chromium-plated surfaces at a dilution of 1: 5 and rinse off with plenty of water.

Wood

Dilute GLOUROS Natural Siding & Masonry Cleaner No. 1806 with water 1: 10 and spray on the surface, scrub the dirt with a non-abrasive pad (normally white) or a sponge until all dirt is removed, then rinse off. Spray the surface with GLOUROS Natural Siding & Masonry Cleaner No. 1806 diluted 1: 5 and allow to dry without rinsing.

For an after-treatment for external application in dry, warm weather conditions and after testing the wood moisture content; use ADAO External Primer No. 259 and KALDET All Weather Stain No. 281, or any other suitable LIVOS products.

Important tips The reaction time depends on the density and the age of the soiling. Always do a test application to check the surface's compatibility with GLOUROS Natural Siding & Masonry No. 1806 and watch the effect.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

Last updated 04-12-2008 12:19

[Back](#)