

Technical Data Sheet

SALIS Finger Paints No. 905

PDF	SALIS Finger Paints No. 905
Application range	For all absorbent materials such as wood, stone, unglazed potter s clay, e.g. paper, cardboard, gypsum, or play dough.
Technical qualities	Tested according to German Industrial Norm (DIN) EN 71 part 1 penetration depth and part 3 suitable for toys.
Full declaration	Water, mineral pigments, methyl cellulose, hemp oil, and extract of gentian roots. Preserved with substances permitted in the pharmaceuticals and food industry.
Colors	011 yellow 051 red 101 black 111 green 121 blue 202 white
	All colors are inter-mixable.
Preparation	Test on the appropriate surface or underground.
Application method	Stir thoroughly! Use a clean spoon or spatula to remove the paint. Apply undiluted or diluted with water, using a brush, sponge, or your fingers.
Drying time	24 hours.
Specific gravity	1,0 1,2 g/ml according to the color.
Safety advice	Not suitable for children under the age of 36 months. Please note that SALIS can dye textiles. Attention: Stains on textiles may be permanent. Protective clothing is recommendable. Please treat any water resistant surface with LANON Toy Stain No. 210 to keep the resistancy.
Disposal	According to locally regulated laws.
Container sizes	A set with 6 x 0.05 l.
Storage	Cool and dry. Please see label for expiry date. Once opened, keep product in the refrigerator and use it as soon as possible. Do not return residual paint into the original container, as there is danger of microbial contamination.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

Last updated 05-12-2008 09:30

[Back](#)