

Technical Data Sheet

GLOUROS Natural Siding & Masonry Cleaner No. 1806

Suitable for	Interior and exterior wooden- and stone surfaces such as tiles, gravestones, walls, decks and facades. Not suitable for marble, calcareous stone or other material sensitive to acid e.g. terrazzo.
Technical qualities	Removes chalk- and cement residue, moss, algae, fungal stains and salt deposits on facades. (Dissolves oil, grease- and protein staining, completely or partially) depending on the surface.
Full declaration	Water, citric acid, Reetha extract.
Dilution	Depending on the density and the amount of dirt/staining, dilute with water at the ratio of 1:10 for cleaning and at the ratio of 1:5 for after-treatment.
Application method	With a sponge, a spray bottle, or a high pressure cleaner.
Cleaning	Clean tools immediately after use with plenty of water.
Specific gravity	1.09 g/ml.
Safety advice	Keep out of the reach of children. Product reacts acidic. Protect skin and eyes during application. In case of contact rinse thoroughly with water. In case of eye contact, seek medical advice immediately. The surfactants used are in accordance with the regulation for detergents No 648/2004 biodegradable. Non-ionic surfactants: less than 5%.
Disposal	According to locally regulated laws.
Container sizes	1.0 lt; 10 lt
Storage	Cool and dry

See reverse for application instructions.

Application	Apply with a sponge or a spraying device on the objects or surfaces to be treated. Rub the dirt off with a non-abrasive pad (normally white) or a sponge and flush or rinse with plenty of water.
Fungi, moss, algae	To clean apply GLOUROS No. 1806 at a ratio of 1: 10. To protect the surface against new fungi spray again with a dilution of 1: 5 and allow to dry.
Salt deposits on facades	The surface should be watered well. Spray surface with a dilution of 1: 20. Rinse off with plenty of water and low pressure.
Metals	Clean light mineral stains on brass, copper and stainless steel with a dilution of 1: 5 to 1: 20. For chalk deposits on chrome surfaces clean with a dilution of 1: 5.
Wood	Dilute GLOUROS No. 1806 with water 1: 10 and spray on, scrub the dirt with a non-abrasive pad (normally white) or a sponge until the dirt dissolves, then rinse. Afterwards spray the surface with a dilution of 1: 5 and let dry. If the old paint is weathered, the surface should be treated after checking the wood moisture content in dry, warm weather. Use ALIS Decking Oil No. 579 for the exterior, otherwise indoors use KALDET Transparent Wood Stain No. 270 or any other suitable LIVOS products. If the paint is weathered down to the bare wood, a recoating is necessary with a suitable paint system.
Important tips	The reaction time depends on the density and the age of the dirt/staining. Always do a test application to check the surface's compatibility with GLOUROS No. 1806 and observe the effect.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction.

No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

March 2011 Rev. 2.1