

according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

GRAVA Wall Primer Sealer No. 408

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

On interior surfaces, to stabilize slightly sandy, chalky or highly absorbent surfaces. As an adhesion agent for LIVOS wall paint coatings.Can also be used as a primer for wallpapering on gypsum boards with LAVO Natural Wall Paper Paste No. 535.

1.3. Details of the supplier of the safety data sheet

Company name:	LIVOS Pflanzenchemie Forschung	ıs- und
	Entwicklungs GmbH & Co. KG	
Street:	Auengrund 10	
Place:	D-29559 Wrestedt	
Telephone:	+49(0)5825-88-0	Telefax:+49(0)5825-8864
e-mail:	info@livos.de	
Internet:	www.livos.de	
Responsible Department:	Produktsicherheit / Product Safety,	, Email: service@livos.de
1.4. Emergency telephone	+49 (0)6132-84463 (24h - GBK Gn	nbH)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

2.2. Label elements

Precautionary statements P102

Keep out of reach of children.

Special labelling of certain mixtures

Contains limonene (orange oil). May produce an allergic reaction.

2.3. Other hazards

EUH208

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Water, linseed oil, isoaliphates, beeswax, methyl cellulose, larch resin, dammar resin, shellac, borax, orange oil, silver chloride, rosemary oil and ethanol.



according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 2 of 8

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to	Regulation (EC) No. 1272/2008 [(CLP]		
90622-58-5	Isoaliphate			1 - < 10 %	
	918-167-1		01-2119472146-39		
	Asp. Tox. 1; H304	·			
1303-96-4	disodium tetraborate deca	hydrate; borax decahydrate		.1 - < 1 %	
	215-540-4	005-011-01-1			
	Repr. 1B; H360FD				
64-17-5	ethanol, ethyl alcohol			< .1 %	
	200-578-6	603-002-00-5			
	Flam. Liq. 2; H225				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

Wash the affected area with soap and water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.



according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 3 of 8

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

When using do not eat, drink, smoke, sniff.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Keep container tightly closed. Keep away from heat. Protect from sunlight.

Advice on storage compatibility

No special measures are necessary.

7.3. Specific end use(s)

On interior surfaces, to stabilize slightly sandy, chalky or highly absorbent surfaces. As an adhesion agent for LIVOS wall paint coatings.Can also be used as a primer for wallpapering on gypsum boards with LAVO Natural Wall Paper Paste No. 535.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1303-96-4	Disodium tetraborate, decahydrate	-	5		TWA (8 h)	WEL
Ĩ		-	-		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 4 of 8

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Eye/face protection

Eye glasses with side protection

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid		
Odour:	transparent characteristic		
	Characteristic		
			Test method
pH-Value (at 20 °C):		8,0	
Changes in the physical state			
Melting point:		not determined	
Initial boiling point and boiling range:		not determined	
Flash point:		> 61 °C	
Flammability			
Solid:		not applicable	
Gas:		not applicable	
Lower explosion limits:		not determined	
Upper explosion limits:		not determined	
Auto-ignition temperature			
Solid:		not applicable	
Gas:		not applicable	
Decomposition temperature:		not determined	
Oxidizing properties			
Not oxidizing.			
Vapour pressure:		not determined	
Density (at 20 °C):		0,98 g/cm³	
Water solubility:		insoluble	
Solubility in other solvents not determined			
Partition coefficient:		not determined	



according to Regulation (EC) No 1907/2006

	GRAVA Wall Primer Sealer No. 408	
Print date: 10.08.2016	Product code: 408	Page 5 of 8
Vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		
Solid content:	not determined	

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
90622-58-5	Isoaliphate				
	oral	LD50	> 5000 mg/kg	Rat	
	dermal	LD50	> 5000 mg/kg	Rabbit	
64-17-5	ethanol, ethyl alcohol	_		-	
	oral	LD50	6200 mg/kg	Rat	IUCLID
	inhalative (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 6 of 8

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

No data available

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
90622-58-5	Isoaliphate					
	Acute fish toxicity	LC50	> 1000 mg/l	96 h	fish	
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h	Daphnia magna	
64-17-5	ethanol, ethyl alcohol					
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h	Daphnia magna	IUCLID

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1303-96-4	disodium tetraborate decahydrate; borax decahydrate	-1,53
64-17-5	ethanol, ethyl alcohol	-0,31

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 7 of 8

Land transport (ADR/RID)

Other applicable information (land transport)

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of these transport regulations.

Air transport (ICAO)

Other applicable information (air transport)

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory	information
---------------	-------------

2010/75/EU (VOC):	
2004/42/EC (VOC):	

2,94 % 2,94 % (28,8 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Water contaminating class (D):

2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances



according to Regulation (EC) No 1907/2006

GRAVA Wall Primer Sealer No. 408

Print date: 10.08.2016

Product code: 408

Page 8 of 8

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H360FD	May damage fertility. May damage the unborn child.
EUH208	Contains limonene (orange oil). May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)