


Technical Data Sheet

KUNOS Floor Maintenance No. 1862

Application range	For maintaining interior wooden floorings previously coated with KUNOS Natural Floor Sealer No. 241, KUNOS Natural Oil Sealer No. 244, KOIMOS High Solid Floor Oil No. 208 or ARDVOS Universal Wood Oil No. 266.
Technical qualities	Refreshes the surface shine and produces a transparent, satin-glossy finish.
Full declaration	Linseed oil - stand oil - natural resin ester, isoaliphates, wood oil – stand oil, natural resin ester, dehydrated amino sugar and drying agents free of lead.
Colors	clear 002
Dilution	Ready to use.
Application method	With a wadded cloth or a polishing machine and a felt pad, at temperatures above 15°C (59°F).
Coverage	6 ml/m ² . Coverage could be considerably less, depending on the absorbency and condition of the surface. Always do a test application first!
Cleaning	Clean equipment immediately after use with LEVO Brush Cleaner No. 997.
Drying time	At 23 °C (73 °F) and 50% relative humidity: 5 hours.
Specific gravity	Approximately 0.82 g/ml.
Safety advice	Provide enough ventilation after application.

Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with KUNOS Floor Maintenance No. 1862 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content.

The product itself will not combust spontaneously.
Contains Cobalt (2+) salts. Can cause allergic reactions.



Irritant

R 43 May cause sensitisation by skin contact.
S 2 Keep out of the reach of children.
S 24 Avoid contact with skin.
S 37 Wear suitable gloves.
S 62 If swallowed do not induce vomiting; seek medical advice immediately and show this container or label.

Disposal	According to locally regulated laws.
Container sizes	0.25 l; 5 l; 30 l.
Storage	Cool and dry. Please see label for expiry date. See reverse for application instructions.

How to use

KUNOS Floor Maintenance No. 1862

Preparation	The KUNOS surface to be treated must be dry, clean and dust free.
Application	Stir thoroughly before use. Remove possible skin formed on surface. Spray some drops (approx. 5g/m ²) of KUNOS Floor Maintenance No. 1862 onto the surface to be treated, and spread immediately using a polishing machine with a felt pad. While polishing, try to avoid the formation of streaks by inspecting the surface against the light. Redo when necessary.
Cleaning	Clean with TRENA pH-Neutral Cleaner No. 556 added to water, and wipe moist but not wet.
Care	After-care can be done with KUNOS Floor Maintenance No. 1862 according to need but at least a couple of times a year.
Important tips	If an abrasive pad is used for the polishing procedure, the color intensity of an existing KUNOS coating might decrease.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

October 2008